



V & W SERIES | 10-15 HP RECIPROCATING COMPRESSORS

## Pump Model WTR

### Customized Solutions

Gardner Denver oil-less compressors are designed to meet the most precise standards for compressed air purity in industrial and medical facility applications. With advanced design features and a system that combines quality, durability and state-of-the-art lubrication technology, the V & W Series offers freedom from oil...freedom from maintenance...freedom from noise...freedom from worry.

### Standard Features

- Totally dry crankcase
- Oil-less compressor service—"O" ring bumper eliminates end wear
- Nickel-plated, cast-iron cylinders
- Long-lasting ball bearing design
- High-grade steel valve plates and reeds
- Cantilevered crankshaft design for superior balance and long life
- Spring-isolated base
- Meets NFPA guidelines for medical air compressors
- 1-Year package warranty
- 1-Year pump warranty

### Available Options

- Control panel
- Fusible disconnect switches
- Automatic tank drain
- Flexible discharge line
- Vibration isolators
- Vinyl-lined or galvanized receivers
- Water-cooled aftercooler
- Remote intake air filter/silencer
- High temperature shutdown/lag
- Compressor alarm
- Air dryer and bypass piping
- Downstream filter banks and indicator

**Gardner**  
**Denver**

## BARE PUMP

MODEL	APPROX. SHIP WEIGHT LBS.	BORE DIA. INCHES	STROKE INCHES	# OF CYLINDERS	DISPLACEMENT CFM MAX	COOLING AIR FLOW MAX CFM @ 175 PSI	HEAT REJECTION MAX BTU/HR	COOLING WATER FLOW GPM	MAX PUMP RPM
WTR	780	4.72 × 3.54	1.97	3	57.8	3650	30500	2	1450

## SIMPLEX BASE MOUNTED UNITS

MOTOR HP	V & W SERIES CIBVWA	DIMENSIONS L × W × H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				125 PSIG	175 PSIG
10	10WTR45	57.3 × 37.5 × 37.4	1155	36	35.4
15	15WTR45	57.3 × 37.5 × 37.4	1195	48.4	48

## SIMPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CISVWA	DIMENSIONS L × W × H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					125 PSIG	175 PSIG
10	120	12T10WTR45	69 × 37.5 × 67	1570	36	35.4
10	250	25T10WTR45	92 × 37.5 × 73	2145	36	35.4
15	120	12T15WTR45	69 × 37.5 × 67	1725	48.4	48
15	250	25T15WTR45	92 × 37.5 × 73	2145	48.4	48

## DUPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CIDVWA	DIMENSIONS L × W × H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					125 PSIG	175 PSIG
10 (2)	120	12TD10WTR45	88.3 × 57.3 × 60.5	2820	72	70.8
10 (2)	250	25TD10WTR45	84 × 67 × 72	3220	72	70.8
15 (2)	120	12TD15WTR45	88.3 × 57.3 × 60.5	3060	96.8	96
15 (2)	250	25TD15WTR45	84 × 67 × 72	3480	96.8	96

## VERTICAL TWO-STAGE, CABINET ENCLOSED

MOTOR HP	V & W SERIES CICVWA	DIMENSIONS L × W × H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				125 PSIG	175 PSIG
10	10EWTR45	40 × 37 × 65.8	1096	36	35.4
15	15EWTR45	40 × 37 × 65.8	1244	48.4	48

**Gardner  
Denver®**


**Gardner Denver, Inc.**

1800 Gardner Expressway  
Quincy, IL 62305  
866-440-6241

[www.gardnerdenver.com/gdproducts](http://www.gardnerdenver.com/gdproducts)



©2018 Gardner Denver, Inc. Printed in U.S.A.  
GRCS-VW-WTR 1st Ed. 2/18





V & W SERIES | 15 HP RECIPROCATING COMPRESSORS

## Pump Model WTS

### Customized Solutions

Gardner Denver oil-less compressors are designed to meet the most precise standards for compressed air purity in industrial and medical facility applications. With advanced design features and a system that combines quality, durability and state-of-the-art lubrication technology, the V & W Series offers freedom from oil...freedom from maintenance...freedom from noise...freedom from worry.

### Standard Features

- Totally dry crankcase
- Oil-less compressor service—"O" ring bumper eliminates end wear
- Nickel-plated, cast-iron cylinders
- Long-lasting ball bearing design
- High-grade steel valve plates and reeds
- Cantilevered crankshaft design for superior balance and long life
- Spring-isolated base
- Meets NFPA guidelines for medical air compressors
- 1-Year package warranty
- 1-Year pump warranty

### Available Options

- Control panel
- Fusible disconnect switches
- Automatic tank drain
- Flexible discharge line
- Vibration isolators
- Vinyl-lined or galvanized receivers
- Water-cooled aftercooler
- Remote intake air filter/silencer
- High temperature shutdown/lag
- Compressor alarm
- Air dryer and bypass piping
- Downstream filter banks and indicator

**Gardner**  
**Denver**

## BARE PUMP

MODEL	APPROX. SHIP WEIGHT LBS.	BORE DIA. INCHES	STROKE INCHES	# OF CYLINDERS	DISPLACEMENT CFM MAX	COOLING AIR FLOW MAX CFM @ 175 PSI	HEAT REJECTION MAX BTU/HR	COOLING WATER FLOW GPM	MAX PUMP RPM
WTS	690	4.72	2.36	3	86.7	2870	30500	2	1140

## SIMPLEX BASE MOUNTED UNITS

MOTOR HP	V & W SERIES CIBVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				50 PSIG	100 PSIG
15	15WTS55	57.3 x 37.5 x 37.4	1180	69	56.5

## SIMPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CISVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					50 PSIG	100 PSIG
15	120	12T15WTS55	69 x 37.5 x 67	1725	69.0	56.5
15	250	25T15WTS55	92 x 37.5 x 73	2145	69.0	56.5

## DUPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CIDVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					50 PSIG	100 PSIG
15 (2)	120	12TD15WTS55	88.3 x 57.3 x 60.5	3065	138	113
15 (2)	250	25TD15WTS55	84 x 67 x 72	3440	138	113

## VERTICAL TWO-STAGE, CABINET ENCLOSED

MOTOR HP	V & W SERIES CICVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				50 PSIG	100 PSIG
15	15EWT55	40 x 37 x 65.8	1180	69	56.5

**Gardner  
Denver®**


**Gardner Denver, Inc.**

1800 Gardner Expressway  
Quincy, IL 62305  
866-440-6241

[www.gardnerdenver.com/gdproducts](http://www.gardnerdenver.com/gdproducts)



©2018 Gardner Denver, Inc. Printed in U.S.A.  
GRCS-VW-WTS 1st Ed. 2/18





V & W SERIES | 5-7.5 HP RECIPROCATING COMPRESSORS

## Pump Model VTR

### Customized Solutions

Gardner Denver oil-less compressors are designed to meet the most precise standards for compressed air purity in industrial and medical facility applications. With advanced design features and a system that combines quality, durability and state-of-the-art lubrication technology, the V & W Series offers freedom from oil...freedom from maintenance...freedom from noise...freedom from worry.

### Standard Features

- Totally dry crankcase
- Oil-less compressor service—"O" ring bumper eliminates end wear
- Nickel-plated, cast-iron cylinders
- Long-lasting ball bearing design
- High-grade steel valve plates and reeds
- Cantilevered crankshaft design for superior balance and long life
- Spring-isolated base
- Meets NFPA guidelines for medical air compressors
- 1-Year package warranty
- 1-Year pump warranty

### Available Options

- Control panel
- Fusible disconnect switches
- Automatic tank drain
- Flexible discharge line
- Vibration isolators
- Vinyl-lined or galvanized receivers
- Water-cooled aftercooler
- Remote intake air filter/silencer
- High temperature shutdown/lag
- Compressor alarm
- Air dryer and bypass piping
- Downstream filter banks and indicator

**Gardner**  
**Denver**

## BARE PUMP

MODEL	APPROX. SHIP WEIGHT LBS.	BORE DIA. INCHES	STROKE INCHES	# OF CYLINDERS	DISPLACEMENT CFM MAX	COOLING AIR FLOW MAX CFM @ 175 PSI	HEAT REJECTION MAX BTU/HR	COOLING WATER FLOW GPM	MAX PUMP RPM
VTR	580	4.72 & 2.56	1.97	2	25.9	3340	15260	1	1300

## SIMPLEX BASE MOUNTED UNITS

MOTOR HP	V & W SERIES CIBVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				125 PSIG	175 PSIG
5	5VTR20	57.3 x 37.5 x 37.4	1035	16.1	15.8
7.5	7VTR20	57.3 x 37.5 x 37.4	1115	21.4	21.2

## SIMPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CISVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					125 PSIG	175 PSIG
5	120	12T5VTR20	69 x 37.5 x 67	1480	16.1	15.8
5	250	25T5VTR20	92 x 37.5 x 73	1845	16.1	15.8
7.5	120	12T7VTR20	69 x 37.5 x 67	1545	21.4	21.2
7.5	250	25T7VTR20	92 x 37.5 x 73	1910	21.4	21.2

## DUPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CIDVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					125 PSIG	175 PSIG
5 (2)	120	12TD5VTR20	88.3 x 57.3 x 60.5	2575	32.2	31.6
5 (2)	250	25TD5VTR20	84 x 67 x 72	2935	32.2	31.6
7.5 (2)	120	12TD7VTR20	88.3 x 57.3 x 60.5	2750	42.8	42.4
7.5 (2)	250	25TD7VTR20	84 x 67 x 72	3110	42.8	42.4

## VERTICAL TWO-STAGE, CABINET ENCLOSED

MOTOR HP	V & W SERIES CICVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				125 PSIG	175 PSIG
5	5EVTR20	40 x 37 x 65.8	1053	16.1	15.8
7.5	7EVTR20	40 x 37 x 65.8	1058	21.4	21.2

**Gardner  
Denver®**

**Gardner Denver, Inc.**

1800 Gardner Expressway  
Quincy, IL 62305  
866-440-6241

[www.gardnerdenver.com/gdproducts](http://www.gardnerdenver.com/gdproducts)



©2018 Gardner Denver, Inc. Printed in U.S.A.  
GRCS-VW-VTR 1st Ed. 2/18

Please recycle after use.





V & W SERIES | 5-10 HP RECIPROCATING COMPRESSORS

## Pump Model VTS

### Customized Solutions

Gardner Denver oil-less compressors are designed to meet the most precise standards for compressed air purity in industrial and medical facility applications. With advanced design features and a system that combines quality, durability and state-of-the-art lubrication technology, the V & W Series offers freedom from oil...freedom from maintenance...freedom from noise...freedom from worry.

### Standard Features

- Totally dry crankcase
- Oil-less compressor service—"O" ring bumper eliminates end wear
- Nickel-plated, cast-iron cylinders
- Long-lasting ball bearing design
- High-grade steel valve plates and reeds
- Cantilevered crankshaft design for superior balance and long life
- Spring-isolated base
- Meets NFPA guidelines for medical air compressors
- 1-Year package warranty
- 1-Year pump warranty

### Available Options

- Control panel
- Fusible disconnect switches
- Automatic tank drain
- Flexible discharge line
- Vibration isolators
- Vinyl-lined or galvanized receivers
- Water-cooled aftercooler
- Remote intake air filter/silencer
- High temperature shutdown/lag
- Compressor alarm
- Air dryer and bypass piping
- Downstream filter banks and indicator

**Gardner**  
**Denver**

## BARE PUMP

MODEL	APPROX. SHIP WEIGHT LBS.	BORE DIA. INCHES	STROKE INCHES	# OF CYLINDERS	DISPLACEMENT CFM MAX	COOLING AIR FLOW MAX CFM @ 175 PSI	HEAT REJECTION MAX BTU/HR	COOLING WATER FLOW GPM	MAX PUMP RPM
VTS	565	4.72	1.97	2	57.8	3650	20350	1.5	1450

## SIMPLEX BASE MOUNTED UNITS

MOTOR HP	V & W SERIES CIBVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				50 PSIG	100 PSIG
5	5VTS35	57.3 x 37.5 x 37.4	1030	21.7	16.8
7.5	7VTS35	57.3 x 37.5 x 37.4	1105	31.6	25.9
10	10VTS35	57.3 x 37.5 x 37.4	1120	43	35.2

## SIMPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CISVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					50 PSIG	100 PSIG
5	120	12T5VTS35	69 x 37.5 x 67	1515	21.7	16.8
5	250	25T5VTS35	92 x 37.5 x 73	1875	21.7	16.8
7.5	120	12T7VTS35	69 x 37.5 x 67	1530	31.6	25.9
7.5	250	25T7VTS35	92 x 37.5 x 73	1890	31.6	25.9
10	120	12T10VTS35	69 x 37.5 x 67	1550	43	35.2
10	250	25T10VTS35	92 x 37.5 x 73	1910	43	35.2

## DUPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	V & W SERIES CIDVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
					50 PSIG	100 PSIG
5 (2)	120	12TD5VTS35	88.3 x 57.3 x 60.5	2545	43.4	33.6
5 (2)	250	25TD5VTS35	84 x 67 x 72	1875	43.4	33.6
7.5 (2)	120	12TD7VTS35	88.3 x 57.3 x 60.5	2760	63.2	51.8
7.5 (2)	250	25TD7VTS35	84 x 67 x 72	3125	63.2	51.8
10 (2)	120	12TD10VTS35	88.3 x 57.3 x 60.5	2815	86	70.4
10 (2)	250	25TD10VTS35	84 x 67 x 72	3220	86	70.4

## VERTICAL TWO-STAGE, CABINET ENCLOSED

MOTOR HP	V & W SERIES CICVWA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	CFM DEL'Y	
				50 PSIG	100 PSIG
5	5EVTS35	40 x 37 x 65.8	999	21.7	16.8
7.5	7EVTS35	40 x 37 x 65.8	1004	31.6	25.9
10	10EVTS35	40 x 37 x 65.8	1040	43	35.2

**Gardner  
Denver®**

**Gardner Denver, Inc.**

1800 Gardner Expressway  
Quincy, IL 62305  
866-440-6241

[www.gardnerdenver.com/gdproducts](http://www.gardnerdenver.com/gdproducts)

©2018 Gardner Denver, Inc. Printed in U.S.A.  
GRCS-VW-VTS 1st Ed. 2/18

